


## PRODUCT FEATURES


- IGBT chip in trench FS-technology
- Low switching losses
- $V_{CE(sat)}$  with positive temperature coefficient
- Fast switching and short tail current
- Free wheeling diodes with fast and soft reverse recovery



## APPLICATIONS

- High frequency switching application
- Medical applications
- Motion/servo control
- UPS systems

1.Gate  
2.Collector  
3.Emitter



Type	$V_{CES}$	$I_C$	$V_{CE(sat)}$ $T_J=25^\circ C$	$T_{Jmax}$	Marking	Package
MM40G3T120B	1200V	40A	1.9V	175°C	MM40G3T120B	TO-247

## ABSOLUTE MAXIMUM RATINGS( $T_C=25^\circ C$ unless otherwise specified)

Symbol	Parameter/Test Conditions	Values	Unit	
$V_{CES}$	Collector Emitter Voltage	$T_J=25^\circ C$ 1200	V	
$V_{GES}$	Gate Emitter Voltage	$\pm 20$		
$I_C$	DC Collector Current	$T_C=25^\circ C$ 70	A	
		$T_C=110^\circ C$ 40		
$I_{Cpuls}$	Pulsed collector current, tp limited by $T_{Jmax}$	140		
$P_{tot}$	Power Dissipation Per IGBT	395	W	
$V_{RRM}$	Repetitive Reverse Voltage	$T_J=25^\circ C$ 1200	V	
$I_{F(AV)}$	Average Forward Current	$T_C=95^\circ C$ 40	A	
$I_{Fpuls}$	Diode pulsed current, tp limited by $T_{Jmax}$	80		
$T_{Jmax}$	Max. Junction Temperature	175	°C	
$T_{Jop}$	Operating Temperature	-40~175		
$T_{stg}$	Storage Temperature	-55~150		
Torque	to heatsink	Recommended (M3)	1.1	Nm
Weight			8	g

MacMic Science & Technology Co., Ltd.

Add: #18, Hua Shan Zhong Lu, New District, Changzhou City, Jiangsu Province, P. R. of China

Tel.: +86-519-85163708 Fax: +86-519-85162291 Post Code: 213022 Website: www.macmicst.com

# MM40G3T120B

## IGBT

### ELECTRICAL CHARACTERISTICS ( $T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit
$V_{GE(th)}$	Gate Emitter Threshold Voltage	$V_{CE}=V_{GE}, I_C=1\text{mA}$	5.0	5.8	6.5	V
$V_{CE(sat)}$	Collector Emitter Saturation Voltage	$I_C=40\text{A}, V_{GE}=15\text{V}, T_J=25^\circ\text{C}$		1.9	2.35	
		$I_C=40\text{A}, V_{GE}=15\text{V}, T_J=125^\circ\text{C}$		2.25		
		$I_C=40\text{A}, V_{GE}=15\text{V}, T_J=150^\circ\text{C}$		2.35		
$I_{CES}$	Collector Leakage Current	$V_{CE}=1200\text{V}, V_{GE}=0\text{V}, T_J=25^\circ\text{C}$			100	$\mu\text{A}$
		$V_{CE}=1200\text{V}, V_{GE}=0\text{V}, T_J=150^\circ\text{C}$			10	$\text{mA}$
$I_{GES}$	Gate Leakage Current	$V_{CE}=0\text{V}, V_{GE}=\pm 15\text{V}, T_J=25^\circ\text{C}$	-400		400	$\text{nA}$
$Q_g$	Gate Charge	$V_{CE}=600\text{V}, I_C=40\text{A}, V_{GE}=15\text{V}$		210		$\text{nC}$
$C_{ies}$	Input Capacitance	$V_{CE}=25\text{V}, V_{GE}=0\text{V}, f=1\text{MHz}$		2.8		$\text{nF}$
$C_{res}$	Reverse Transfer Capacitance				110	$\text{pF}$
$t_{d(on)}$	Turn on Delay Time	$V_{CC}=600\text{V}, I_C=40\text{A}$ $R_G=20\Omega,$ $V_{GE}=\pm 15\text{V},$ Inductive Load	$T_J=25^\circ\text{C}$		30	$\text{ns}$
			$T_J=125^\circ\text{C}$		35	$\text{ns}$
			$T_J=150^\circ\text{C}$		40	$\text{ns}$
$t_r$	Rise Time	$V_{GE}=\pm 15\text{V},$ Inductive Load	$T_J=25^\circ\text{C}$		40	$\text{ns}$
			$T_J=125^\circ\text{C}$		45	$\text{ns}$
			$T_J=150^\circ\text{C}$		45	$\text{ns}$
$t_{d(off)}$	Turn off Delay Time	$V_{CC}=600\text{V}, I_C=40\text{A}$ $R_G=20\Omega,$ $V_{GE}=\pm 15\text{V},$ Inductive Load	$T_J=25^\circ\text{C}$		250	$\text{ns}$
			$T_J=125^\circ\text{C}$		290	$\text{ns}$
			$T_J=150^\circ\text{C}$		310	$\text{ns}$
$t_f$	Fall Time	$V_{GE}=\pm 15\text{V},$ Inductive Load	$T_J=25^\circ\text{C}$		100	$\text{ns}$
			$T_J=125^\circ\text{C}$		150	$\text{ns}$
			$T_J=150^\circ\text{C}$		180	$\text{ns}$
$E_{on}$	Turn on Energy	$V_{CC}=600\text{V}, I_C=40\text{A}$ $R_G=20\Omega,$ $V_{GE}=\pm 15\text{V},$ Inductive Load	$T_J=125^\circ\text{C}$		4.9	$\text{mJ}$
			$T_J=150^\circ\text{C}$		5.4	$\text{mJ}$
$E_{off}$	Turn off Energy	$V_{GE}=\pm 15\text{V},$ Inductive Load	$T_J=125^\circ\text{C}$		4.2	$\text{mJ}$
			$T_J=150^\circ\text{C}$		4.7	$\text{mJ}$
$I_{SC}$	Short Circuit Current	$t_{psc} \leq 10\mu\text{s}, V_{GE}=15\text{V}$ $T_J=125^\circ\text{C}, V_{CC}=600\text{V}$		150		A
$R_{thJC}$	Junction to Case Thermal Resistance ( Per IGBT)				0.35	$\text{K/W}$

## Anti-Parallel Diode

### ELECTRICAL CHARACTERISTICS ( $T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit
$V_F$	Forward Voltage	$I_F=40\text{A}, V_{GE}=0\text{V}, T_J=25^\circ\text{C}$		2.05	2.55	V
		$I_F=40\text{A}, V_{GE}=0\text{V}, T_J=125^\circ\text{C}$		1.85		
		$I_F=40\text{A}, V_{GE}=0\text{V}, T_J=150^\circ\text{C}$		1.75		
$t_{rr}$	Reverse Recovery Time	$I_F=40\text{A}, V_R=600\text{V}$ $di_F/dt=-850\text{A}/\mu\text{s}$ $T_J=150^\circ\text{C}$		350		$\text{ns}$
$I_{RRM}$	Max. Reverse Recovery Current			39.5		A
$Q_{RR}$	Reverse Recovery Charge			5		$\mu\text{C}$
$E_{rec}$	Reverse Recovery Energy			1.85		$\text{mJ}$
$R_{thJCD}$	Junction to Case Thermal Resistance ( Per Diode)				0.7	$\text{K/W}$

# MM40G3T120B




Figure 1. Typical Output Characteristics IGBT




Figure 2. Typical Output Characteristics IGBT




Figure 3. Typical Transfer characteristics IGBT




Figure 4. Switching Energy vs Gate Resistor IGBT




Figure 5. Switching Energy vs Collector Current IGBT




Figure 6. Reverse Biased Safe Operating Area IGBT

# MM40G3T120B




Figure 7. Collector Current vs Case temperature IGBT




Figure 8. Forward current vs Case temperature Diode




Figure 9. Diode Forward Characteristics Diode




Figure 10. Switching Energy vs Gate Resistor Diode




Figure 11. Switching Energy vs Forward Current Diode





Figure 12. Transient Thermal Impedance of Diode and IGBT



Dimensions in (mm)  
Figure 13. Package Outline